



Hammond XK-5 Specifications

Manuals Upper and Lower 73 notes each (61 playing keys plus 12 Preset Keys) Square-front ("waterfall"-style) New mechanical key-bed design	Vibrato & Chorus™ Virtual Scanner™ (3 settings) Adjustable rate Vibrato/Chorus Mix Vibrato on Pedal ON/OFF	Reverb ON/OFF panel control 11 programs Leslie On Reverb ON/OFF
Pedal (optional) 13, 20-note spinet-style 25-note radiating Adjustable Pedal Sustain Pedal to Lower coupler Custom Pedal Registrations (3 Factory, 3 User)	Overdrive Tube/Solid State Adjustable drive level	MIDI 5 MIDI Templates 3 Keyboard Channels (Upper, Lower, Pedals) 6 External Zones (3 Upper, 2 Lower, 1 Pedals) Assignable MIDI channels Key range Program Change Pan Velocity Curve Min/Max Volume IN 1, IN 2, OUT Connections
Split SPLIT panel control Assignable split point	Patches 100 User, 100 Factory Patches Assignable to Preset Keys as Favourites Assignable Patch Load: • Drawbar registrations • Drawbar parameters • Internal & External Zones • Multi - Effects • Reverb	Display OLED, 20 character, 2 line 7 Control Buttons & VALUE Rotary Knob
Tone Generator MTW™ (Modeled Tone Wheels) 61-note polyphony for Manuals 5-note polyphony for Pedals	Preset Keys 9 Presets plus Cancel each Manual 2 Adjust Presets each Manual 9 programmable Preset Banks	USB "A" port ("To USB Flash Drive") "B" port ("To Host")
Virtual Multi-Contacts™ Custom Contacts (3 Factory, 3 User) 3 Physical Contacts, 9 Assignable Virtual Contacts Adjustable Attack, Release, Decay	Tube Preamp 12AU7/12AX7 Tubes Adjustable Routing & Drive Level	Tune/Transpose Transpose ± 6 semitones Fine Tune ± 10 cents Octave Up/Down ± 2 octaves
Harmonic Drawbars® 5 sets (4 Manuals, 1 Pedal) Upper 2 X 9 pitches Lower 2 X 9 pitches Pedal 2 pitches	MT™ Matching Transformer Adjustable drive level Hysteresis Upper/Lower/Percussion levels	H-BUS® Connector To Pedals/Expression Pedal
Drawbar Voicing 4 choices for Manuals (A-100, B-3, C-3, Mellow) 4 choices for Pedals (Normal, Muted, Synth 1 & 2)	Multi-Effects • Tremolo • AutoPan • Wah-Wah • Ring Modulator • Phaser • Flanger • Chorus • Delay Adjustable parameters for each effect.	Audio Connections LINEOUT L/MONO/R Headphone Jack
Custom Tone Wheel (CTW™) 3 Factory, 3 User for A-100, B-3, C-3 & Mellow Drawbar Voicings CTW's identified by model and serial number Adjustable parameters for each tone wheel 12 complex tone wheels for bottom 12 pedal tones	Master Equalizer Bass/Mid/Treble panel controls Adjustable gain & center frequency	11-pin Leslie® Connector
Touch-Response Percussion™ Percussion On Normal/Soft Volume Slow/Fast Decay 2nd & 3rd Harmonic Adjustable Normal/Soft Volume settings Slow/Fast Decay rates Velocity Key Tracking 1' Drawbar Cancel ON/OFF	Programmable Equalizer Bass, Mid, Treble Adjustable center frequency Hammond Preamp Tone Control	Other Connections CONTROL 1, CONTROL2 8-pin DIN (EXP-100F Expression Pedal) AC Input
	Leslie® STOP, FAST, BYPASS panel controls Custom Cabinets (8 Preset, 8 User) Adjustable Slow & Fast Speeds Rise & Fall Times Horn/Drum/Subwoofer Volume Balance Microphone Settings	Dimensions 46.8"(W) 15.8" (D) 4.7" (H) Weight 34.6 lbs 15.7kg

HAMMOND ORGANS AUSTRALIA

www.harmondorgans.com.au

BERNIES MUSIC LAND

381 Canterbury Road, Ringwood

Tel: 9872 5122

www.musicland.com.au

info@musicland.com.au